

AMENDMENTS TO THE SPECIFICATION

Please replace paragraph [0035] with the following amended paragraph:

[0035] Meanwhile, a plurality of storing parts 23 for storing the detergent are formed inside the detergent box 24. And, a cover 30 is provided to a topside of the detergent box 24 to open/close the storing parts 23. The cover 30 is rotatably fixed to a cover frame 40 that is assembled to the detergent box 24. In this case, the cover 30 is coupled to the cover frame 40 using a hinge.

Please replace paragraphs [0042] – [0044] with the following amended paragraphs:

[0042] The hooks 25a are formed at front and rear sides of the detergent box 24, and the holes 17a are formed to correspond to the hooks 25a, respectively. Once the hooks 25a are coupled to the holes 17a, respectively, the detergent box 24 is securely fixed to the opening 16a.

[0043] Meanwhile, the detergent box 24 is inserted to lie under the opening 16a. In doing so, the hooks 25a are inserted in the holes 17a to be fixed thereto.

[0044] The hooks 25a formed at the detergent box 24, as shown in FIG. 4, are inserted in ~~thee~~the holes 17a formed at the bent part 17b, respectively. Moreover, the bent part 17b reinforces rigidity of a neighbor part 16b of the opening 16a.

Please replace paragraph [0048] with the following amended paragraph:

[0048] One ends of the second bosses 41b are inserted in the first holes 25b, respectively, whereby the holes 41a and 25b coincide with each other with ease. Each of the screws 50

penetrates the corresponding holes 41a and 25b to be locked. Hence, the cover frame 40 and the detergent box 24 are more easily fixed to the neighbor part 16b of the opening 16.

Please replace paragraph [0051] with the following amended paragraph:

[0051] Namely, interior screws coupled to the screws 50 are formed on the lower inner circumferences 25f of the first holes 25b, respectively, and the screws 50 are coupled to the interior screws, respectively. In doing so, the neighbor part 16b of the opening 16a is strongly clamped between the cover frame 40 and the hooks 25a of the detergent box 24. Namely, the detergent box 24 and the cover frame 40 clamp the top plate 16 to be fixed thereto.

Please replace paragraph [0053] with the following amended paragraph:

[0053] First of all, ~~less~~less efforts are made to alignment between the holes of the detergent box and cover frame. Namely, while the hooks of the detergent box are caught on the top plate, the first bosses are inserted in the second bosses. The screws are then coupled to fix the detergent box to the top plate simply.